

New generation of polycarboxylic ether plasticizer, specially designed for use in Manufactured Concrete Products

Description of Product

RheoFIT[®] 757 is an innovative multi-purpose plasticizer based on polycarboxylic ether polymers, specially developed for earth-dry concrete. At the same time, RheoFIT[®] 757 accelerates the strength development, increases the tolerance to changes in moisture content and reduces the cycle time whilst the appearance is maintained or even improved.

Thanks to its unique principle of action on the cement grain, RheoFIT[®] 757 fully exploits the hydration potential of cement resulting in higher early strengths and shorter curing times.

FIT 4 VALUE:

RheoFIT[®] 757 is a key component to BASF's FIT 4 VALUE concept.

FIT 4 VALUE considers the four elements essential for MCP Manufactures:

- FIT for Economics
- FIT for Performance
- FIT for Aesthetics
- FIT for Durability

Here, FIT means meeting every requirement for economics, performance, aesthetics and durability.

Fields of Application

RheoFIT[®] 757 is suitable for Manufacturing Concrete Products, especially:

- Pavers
- Pipes & Drainage Products
- Blocks

Features and Benefits

RheoFIT[®] 757 offers the following benefits for the MCP industry to:

- Optimised mix design
- Increased tolerance to variation of moisture content in the mix and consequently, more homogenous mix properties
- Enhanced productivity due to shorter cycle time
- Higher early strength
- Optimised curing cycles due to shorter curing times

Technical Data/Typical Properties

Appearance	Light brown to yellow liquid
Specific gravity @ 20°C	1.07 g/cm ³
pH-value	7.5
Alkali content (%)	Less than or equal to 2.0
Chloride content (%)	Less than or equal to 0.10
Chlorine content (%)	Less than or equal to 0.10

Application Procedure

RheoFIT[®] 757 is a liquid ready-to-use admixture to be added to the concrete during the mixing process. The best results are obtained when the admixture is added after all the other components are already in the mixer and after the addition of at least 80% of the total water. The water content is adjusted to obtain the desired consistence or workability.

Dosage rate

The normally recommended dosage rate is 0.3 to 0.8 litres per 100 kg of cement.

Other dosages may be used in special cases according to specific job site conditions. In this case please consult our Technical Services Department.

Compatibility

RheoFIT[®] 757 is compatible and recommended for use with:

- RheoFIT[®] 742, colour enhancer
- RheoFIT[®] 743/744, water repellent, to reduce water absorption (e.g. EN 1338, class 2 B)
- Rheofinish[®] 299C, cleaning and protection agent
- Rheofinish[®] 314J and 340M, form release agent, to enhance appearance

RheoFIT[®] 757 is not compatible with the RHEOBUILD[®] and GLENIUM[®] superplasticizers.

Packaging

RheoFIT[®] 757 is available in 25 litre containers, 205 litre drums and 1000 litre (IBC) tanks.

Storage

RheoFIT[®] 757 must be stored in a place where temperature does not drop below +5°C. If product has frozen, thaw at +3°C and agitate until completely reconstituted. Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult our Technical Services Department.

Self Life

If stored in unopened containers according to manufacturer's instructions, the shelf life is 12 months.

Handling and transportation

No special requirements must be observed while the product is used. Protection gloves and glasses are recommended. Do not eat, drink or smoke during the application. RheoFIT[®] 757 is non-flammable, non-toxic or irritant and is not subject to special transport requirements.

BASF Construction Chemicals (UK) Ltd,
Albany House,
Swinton Hall Road,
Swinton,
Manchester M27 4DT
Tel: +44 (0) 161 794 7411
Fax +44 (0) 161 727 8547
www.basf-cc.co.uk

RheoFIT[®] 757, BASF Construction Chemicals (UK) Limited, Version 2

Health and Safety

*For full information on Health and Safety matters regarding this product the relevant Health and Safety Data Sheet should be consulted.

The following general comments apply to all products.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs, (which may also be tainted with vapour until the product is fully cured and dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek medical attention. Keep away from children and animals. Reseal containers after use.

Spillage

Chemical products can cause damage; clean spillage immediately.

DISCLAIMER

"BASF Construction Chemicals (UK) Limited" (the Company) endeavours to ensure that advice and information given in Product Data Sheets, Method Statements and Material Safety Data Sheets (all known as Product Literature) is accurate and correct. However, the Company has no control over the selection of its products for particular applications. It is important that any prospective customer, user or specifier, satisfies him/her-self that the product is suitable for the specific application. In this process, due regard should be taken of the nature and composition of the background/base and the ambient conditions both at the time of laying/applying/installing the material and when the completed work is to be brought into use.

Accordingly, no liability will be accepted by the Company for the selection, by others, of a product, which is inappropriate to a particular application.

Products are sold subject to the Company's standard conditions of sale and all customers, users and specifiers, should ensure that they examine the Company's latest Product Literature.